

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 0932084

(43) Date of publication of application: 12.12.1

(51) Int. Cl. H01F 7/16
H01F 7/121

(21) Application number: 08160700
(22) Date of filing: 30.05.1996

(71) Applicant: AICHI ELECTRIC CO LTD
(72) Inventor: MOCHIZUKI KOICHIRO
TAKASU YUJI

(54) SOLENOID DEVICE


(57) Abstract:

PROBLEM TO BE SOLVED: To enable economical manufacture with a simple structure for efficiently driving a solenoid valve, by forming a guide member for lifting and guiding a moving core using a non-magnetic material and a magnetic material.

SOLUTION: In a solenoid device, a support cylinder 8 of a guide member 8a located between a yoke 7 and a moving core 4 is made of a magnetic material. The support cylinder 8 is welded to a guide cylinder 4a having a shape with a step and made of a non-magnetic material, in such a manner as to make a gap between the support cylinder 8 and the moving core 4 as narrow as possible, thereby constituting the guide member 8a. Thus, in the solenoid device, the guide member 8a of the moving core 4 is easily welded to a welding point d using electron-beam welding. In addition, the electron-beam welding causes high-speed thermoelectrons to collide with a welding target portion in a vacuum, so as

to melt up to a target layer portion, and does not gas contamination to the molten metal.

COPYRIGHT: (C)1997,JPO



(16)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number 09320840 A

(43) Date of publication of application 12.12.1997

(51) Int. Cl. H01F 7/16
H01F 7/121(71) Applicant number 08160700
(22) Date of filing 30.03.1996(71) Applicant AICHI ELECTRIC CO. LTD.
(72) Inventor MOCHIZUKI KOICHIRO
TAKASU YUJI

(34) SOLENOID DEVICE

(37) Abstract

PROBLEM TO BE SOLVED: To enable convenient manufacturing with a simple structure by effectively directing a magnetic flux, by forming a guide member for lifting and guiding a moving core using a non-magnetic material and a magnetic material.

SOLUTION: In a solenoid device, a support cylinder 8 of a guide member 4 is formed between a yoke 7 and a moving core 4 is made of a magnetic material. The support cylinder 8 is welded to a guide cylinder 4a having a shape with a step and made of a non-magnetic material, in such a manner as to make a gap between the support cylinder 8 and the moving core 4 as narrow as possible, thereby controlling the guide member 4a. Thus, in the solenoid device, the guide member 4a of the moving core 4 is easily welded to a welding point d using electron-beam welding. In addition, the electron-beam welding causes high pressure and a selective force to melt both a welding target portion in a common area.

to melt up to a target layer portion, and does not cause gas contamination to the molten metal.

COPYRIGHT: (C) 1997 JPO

